

DESIGN & PERFORMANCE

Sleek, modern and built with durable stainless steel, the Roti-Roaster rotisserie combines elegance with functionality. Its "ROTISSERIE" screen-printed glass doors and powerful interior lighting beautifully showcase your products while they cook. Designed for efficiency, it features a front-load and rear door design, passthrough, for optimal performance.

Cleaning is effortless with removable accessories, interior panels, and a drip pan, ensuring convenience and hygiene. Engineered for high output, rapid cooking, and superior roasting, this rotisserie is built to last. Fully insulated with energy-efficient heating elements, it minimizes energy consumption while maximizing performance *helping you save on costs without compromising quality.*

ENERGY & COST-EFFICIENT K-GLASS

Designed for superior energy efficiency, the Roti-Roaster features insulated, double-glazed K-GLASS doors. The inner pane is coated with a specialized thin metal layer that regulates heat transfer, providing exceptional resistance to thermal radiation. This advanced design reduces energy consumption, lowers operational costs, and maximizes savings.

Additionally, K-GLASS minimizes heat emission in the kitchen, creating a cooler and more comfortable workspace for your team. The enhanced insulation also improves safety by preventing burns upon contact with the door surfaces, ensuring a secure cooking environment.



CONTROL PANEL



Standard (Default)

With 6 preset programs
+ manual control



Touch (Optional)

Multiple recipes + manual control
(+ can add up to 99 programs)

FBPT16.760




TECHNICAL CHARACTERISTICS

- Fully insulated with rock wool (Bio-soluble aluminum encapsulation)
- K-Glass thermal double glazing mounted on silicone seal (anti-scald front panel)
- Control panel with 6 cooking programs
- Delivered with cooking baskets BALD720
- Enters auto hold at the end of the cooking cycle

ACCESSORIES (OPTIONAL)

BALD720 Basket for poultry	BAP720 Small cuts basket	PD720 Vegetable tray	PLC720 Cooking basket	BCRA720 Spatchcock spit	BV720 Chicken spit (fork)



SPECIFICATIONS

Weight	350kg
Capacity of poultrys	64/80
Number of baskets	16
Doors	2x2 double glazed door (2 anti-scald K.Glass door)
Internal lighting	Halogen lamps protected by glass cover
Power supply	3 Phase (230△400Y3N~)
Electrical power	19kW
Wire length	2m
Temperature and Time control	Digital control or optional TOUCH Screen
Cooking cycle alarm	Yes
Internal presentation	Central axis, support and removable swing trays



FBPT16.760



Revised: March 2025



DISTRIBUTOR / AGENT

Rotisol S.A.S.

Zone industrielle La Trentaine, Avenue Gustave Eiffel

77507 Chelles cedex - FRANCE

s.bennell@rotisol.com - Tel : +33 1 64 21 80 00

www.rotisol.com

